



WALL

ARTCRAFTED™
GLAZED CERAMIC



 daltile®
IMAGINE WHAT'S POSSIBLE™

ARTCRAFTED™

GLAZED CERAMIC

Color and character come together to create Artcrafted, the handcrafted-inspired wall tile and mosaic series. Uneven surfaces and high variation form a bespoke backdrop to any design. Select between warm, creamy neutrals or vibrant accent colors – all available in glossy 4 x 4 & 3 x 12 wall tiles as well as the trendy 1 x 6 mosaic. Mix and match colors and sizes for a true artistic experience.

WALL

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™




C^G GLAZED CERAMIC

LOW HIGH

SPECIAL FEATURES

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.



Cover photo features Artcrafted™ Cotto 3 x 12 glossy wall tile on the wall, Fern 3 x 12 glossy wall tile on the island and Outlander™ Moonlight, Grande design 24 x 24 matte on the floor.

Above photo features Artcrafted™ Tide 4 x 4 on the backsplash and island, Acreage™ Stetson 8 x 48 on the floor, and Natural Stone Marble Carrara Gioia on the countertop.

WALL

ARTCRAFTED™

GLAZED CERAMIC

SIZES:



4 x 4
Wall Tile



3 x 12
Wall Tile



1 x 6
Mosaic

FINISHES: GLOSSY


COLOR PALETTE




COCONUT



DUNE



ALOE




FERN



COTTO



TIDE



DRIFT

3 x 12 WALL TILE



COCONUT AC23



DUNE AC24



ALOE AC25



FERN AC26



COTTO AC27



TIDE AC29



DRIFT AC30

4 x 4 WALL TILE



COCONUT AC23



DUNE AC24



ALOE AC25



FERN AC26



COTTO AC27



TIDE AC29



DRIFT AC30

1 x 6 MOSAIC




COCONUT AC23



DUNE AC24




ALOE AC25



FERN AC26



COTTO AC27



TIDE AC29



DRIFT AC30



STAINPROOF



DENTPROOF



SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	4 x 4 Wall Tile	(3-7/8" x 3-7/8") (9.85 cm x 9.85 cm)	3/8" (10 mm)	5.67	54
	3 x 12 Wall Tile	(3" x 12-1/16") (7.65 cm x 30.70 cm)	5/16" (9 mm)	10.12	40
	1 x 6 Mosaic (Dot-mounted)	(9-3/4" x 11-1/2" Sheet) (24.76 cm x 29.21 cm Sheet)	5/16" (7.90 mm)	8.30	10

Note: 4 x 4 Wall Tile is made in the U.S.A

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	✓*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A1371-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

APPLICATION NOTES :

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

* 1 x 6 mosaic tile only.

TRIM

Type	Number	Size	Pieces/ Carton
 Jolly	S1/212J	1/2 x 12	12

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8"	 High (V3)

PERFORMANCE CHARACTERISTICS

	ASTM#	Wall Result	Mosaic Result
Water Absorption	C373	< 20.0%	< 3.0%
Breaking Strength	C648	120 lbs - 230 lbs	> 250 lbs
Scratch Hardness	MOHS	4.0 - 6.0	4.0 - 6.0
Chemical Resistance	C650	Resistant	Resistant

For additional information on test results, visit us at: daltille.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltille.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltille.com.