

BRYSON VALLEY™

AMERICAN OLEAN®



COLORBODY™ PORCELAIN FLOOR

FLOOR

WOOD LOOK



AMERICAN OLEAN®
PROVEN IN TILE™

BRYSON VALLEY™

Bryson Valley offers an ultra-realistic barnwood visual with authentic hardwood texture. The rich warmth of real wood floors is presented in large format porcelain tile appealing to designers and homeowners who prefer today's longer, wider planks.



COVER PHOTO: PETRIFIED FOREST
ABOVE PHOTO: COASTAL BEACHWOOD



FLOOR

FINISHES: MATTE

USAGE



MATERIAL



PRICING



SPECIAL FEATURES



WOOD LOOK

COLORBODY™ PORCELAIN FLOOR TILE



COASTAL BEACHWOOD BV10



WHISKEY BARREL BV11



NANTUCKET ESTATE BV12



PETRIFIED FOREST BV13



TRUFFLE BARNWOOD BV14



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT™



FIRE RESISTANT



CLIMATEPRO™



SIMPLICLEAN™

VISIT AMERICANOLEAN.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FLOOR

FINISHES: MATTE


USAGE



MATERIAL



PRICING



SPECIAL FEATURES



WOOD LOOK

SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	8 x 48 Floor Tile	7-3/4" x 46-15/16" (19.71 cm x 119.30 cm)	5/16"	15.19	6

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●
Wet & Level – Interior Floor	≥ 0.42	●
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

INSTALLATION & PRICING

Grout Joint Recommendation	Shade Variation
Floor: 1/8" (3/16" when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)	

PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs.
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: americanolean.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

FEATURES



PRE-CONSUMER
RECYCLED CONTENT



REVEAL IMAGING®



MADE IN THE U.S.A.



All or select items within this series meet the requirements for these qualifications. For more information visit americanolean.com.

888.AOT.TILE

AMERICANOLEAN.COM



AMERICAN OLEAN®
PROVEN IN TILE™

©2020 AMERICAN OLEAN (04/20)