

CHATEAU RESERVE™

COLOBODY™ PORCELAIN FLOOR WITH STEPWISE™ TECHNOLOGY

MARAZZI®
DARE TO BE BOLD™

WOOD LOOK



CHATEAU RESERVE™

Create your personal sanctuary with Chateau Reserve™, a wood-look tile collection designed to evoke the elegance and comfort of a secluded retreat. Available in two rich, refined wood tones, this series brings the beauty of nature to run from outdoor to indoor with Stepwise™ Technology, providing slip resistance and comfort underfoot—without sacrificing style. From cozy living rooms to open-air patios, this collection transforms any space into a warm and welcoming escape.



Cover photo features Chateau Reserve™ Woodland Chalet, 8 x 48 on the floor and Creativo™ Carbon, 24 x 24 on the wall. Above photo features Chateau Reserve™ Hickory Grove, 6 x 48 on the shower wall and 8 x 48 on the floor and Modern Formation™ Smoky Ridge, 24 x 48 on the wall

WOOD LOOK

CHATEAU RESERVE™

COLORBODY™ PORCELAIN FLOOR WITH STEPWISE™ TECHNOLOGY

FINISHES: MATTE

USAGE

FLOOR

WALL

COUNTERTOP

SHOWER FLOOR

EXTERIOR FLOOR

MATERIAL

PC

COLORBODY™

PRICING

LOW

HIGH

SPECIAL FEATURES

STEPWISE™

TRUEEDGE™

REVEAL SYNC3D™

MADE IN THE U.S.A.

LARGE FORMAT

MOSAIC/DECO

ENCAUSTIC

TERRAZZO

PAVER

CUSTOMIZE

WOOD LOOK

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

COLORBODY™ PORCELAIN FLOOR TILE



CR40 Hickory Grove



CR44 Woodland Chalet

SIZES

			Thickness	Finish	Made in U.S.A.
	8 x 48 Floor Tile	7-3/4" x 46-15/16" (19.70 cm x 119.20 cm)	5/16"	M	
	6 x 48 Floor Tile	5-3/4" x 46-15/16" (14.70 cm x 119.20 cm)	5/16"	M	

M Matte Finish

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	■
Wet & Level – Interior Floor	≥ 0.42	■
Shower Floors – Standard Center Drain	≥ 0.42	
Shower Floors – Linear Drain	≥ 0.42 (Mosaic)	
	≥ 0.60 (Floor)	■
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	■
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit marazziusa.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)	V3 High Variation

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbf
Scratch Hardness	C1895	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: marazziusa.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance			
1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	④	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazziusa.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to marazziusa.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

FEATURES

PRE-CONSUMER RECYCLED MATERIALS

REVEAL IMAGING®

CERTIFIED PORCELAIN TILE 100% OF BODY WATER-IMPENETRABLE

ZEROTOX

All or select items within this series meet the requirements for these qualifications. For more information visit marazziusa.com.