



MOSAIC LOOK

DECORATIVE
CLIO™
GLASS & STONE MOSAICS



 **daltile®**
IMAGINE WHAT'S POSSIBLE™

DECORATIVE

CLIO™

GLASS & STONE MOSAICS

Unlock Your Room's Potential

Behold the perfect pairing of sophistication and daring design. Clio™ mosaics from Daltile is a fresh blend of stone and glass in a versatile mosaic. The rich look of polished stone is randomly mixed with glass in glossy and frosted finishes. Stretch your creativity as you contemplate installing it vertically, horizontally or cut down to smaller pieces to be used as accents to another tile. Clio mosaics will win you over time and time again as you proudly admire your unique and stylish new space.

- **UNIQUE GLASS & STONE MOSAIC**
 - These popular materials integrate easily into any style
 - Varied width mosaic is a unique mosaic option
- **EASY INSTALLATION**
 - You can place vertically or horizontally for more design options



MOSAIC LOOK

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



GLASS

LOW HIGH

SEE CHARTS FOR FULL PRODUCT DETAILS

SPECIAL FEATURES

Above and cover photos feature Selene 1 x Random mosaic on fireplace wall.
Floor features Season Wood™ Snow Pine in 12 x 48, 8 x 48, and 6 x 48 random linear pattern on the floor.

SIZES:



1 x Random
Mosaic

FINISHES: MATTE | GLOSSY

1 X RANDOM MOSAIC



SELENE CL16



LUNA CL13



NOX CL14



HERA CL15



EOS CL17



BOREAS CL18

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	1 x Random Mosaic (Mesh-mounted on 12" x 12" Sheet)	(11-3/4" x 11-3/4" Sheet) (29.80 cm x 29.80 cm Sheet)	5/16"	9.60	10

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8"	 Random (V4)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.1%
Breaking Strength	C648	> 100 lbs
Scratch Hardness	MOHS	4.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at:
daltille.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at:
daltille.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.