

HISTORIC BRIDGE™

GLAZED PORCELAIN FLOOR

AMERICAN OLEAN®

WOOD LOOK



AMERICAN OLEAN®
PROVEN IN TILE™

HISTORIC BRIDGE™

Historic Bridge™ perfectly captures the look of exposed and weathered wood, with authentic details like water staining and cracking to worn-paint effects. Three rich colors feature a high level of variance. Special glazing adds to the genuine effect by creating a slight sheen along the graining. All colors are available in a plank size well-suited for creating floors with a rustic look. Historic Bridge answers current demand for organic influences from residential to commercial settings.



Cover and above photos feature Historic Bridge™ Upper Ferry 6 x36 on the floor.

HISTORIC BRIDGE™

GLAZED PORCELAIN FLOOR

AMERICAN OLEAN®

FINISHES: MATTE

USAGE



MATERIAL



PRICING



SPECIAL FEATURES



NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

WOOD LOOK

GLAZED PORCELAIN FLOOR TILE



UPPER FERRY HB01



OLD HOLLOW HB02



OLD FORGE HB04



VISIT AMERICANOLEAN.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

HISTORIC BRIDGE™

GLAZED PORCELAIN FLOOR

AMERICAN OLEAN®

FINISHES: MATTE

USAGE



MATERIAL



PRICING



SPECIAL FEATURES



NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

WOOD LOOK

SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	6 x 36 Floor Tile	5-15/16" x 35-7/16" (15.19 cm x 90.00 cm)	5/16"	13.05	9

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●
Wet & Level – Interior Floor	≥ 0.42	●
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

TRIM

			NUMBER	PIECES/ CARTON
	Floor Bullnose	3 x 18	S43H9	16

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)	 RANDOM (V4)

PERFORMANCE CHARACTERISTICS

	ASTM#	RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs.
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: americanolean.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit americanolean.com.

FEATURES



PRE-CONSUMER
RECYCLED MATERIALS



MADE IN THE U.S.A.



REVEAL IMAGING®



CERTIFIED
PORCELAIN™
TILE
0.05% or less water absorption

ZEROTOX
Healthy Homes | Healthy Planet

All or select items within this series meet the requirements for these qualifications.
For more information visit americanolean.com.

888.AOT.TILE



AMERICAN OLEAN®
PROVEN IN TILE™

AMERICANOLEAN.COM

©2023 AMERICAN OLEAN (11/23)