

HISTORIC LIMESTONE™

COLORBODY™ & GLAZED PORCELAIN AND GLAZED CERAMIC

AMERICAN OLEAN®

STONE LOOK



AMERICAN OLEAN®
PROVEN IN TILE™

HISTORIC LIMESTONE™

Historic Limestone honors the timeless look of limestone with an urban rustic twist. The floor and mosaic assortment revives the appeal of limestone through authentic graphics shown in each piece. Paving the way for design innovation, Historic Limestone beautifully combines the look of limestone and wood. This collection also features Stepwise™ Technology allowing you to extend the visuals of stone from your indoor to outdoor spaces. Celebrate limestone's classic appearance while reaching new heights through a mix of shapes and sizes.



50% MORE
SLIP RESISTANT
THAN ORDINARY TILE*

*When compared to tile meeting ANSI Standards



Cover photo features Tradition and Lineage, 24 x 24 on the floor.

Above photo features Historic Limestone™ Lineage Blend Landmark Hexagon Mosaic on the wall and Union™ Rusted Brown, 24 x 48 on the floor.

HISTORIC LIMESTONE™

COLORBODY™ & GLAZED PORCELAIN AND GLAZED CERAMIC

AMERICAN OLEAN®

FINISHES: MATTE

USAGE	MATERIAL	PRICING	SPECIAL FEATURES
 FLOOR  WALL  COUNTERTOP  SHOWER FLOOR  EXTERIOR FLOOR	 PC  CG  PG	 LOW  HIGH	 STEPWISE™  TRUEDGE™  REVEAL SYNC3D™  MADE IN THE U.S.A.  LARGE FORMAT  MOSAIC/DECO  ENCAUSTIC  TERRAZZO  PAVER  CUSTOMIZE

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

STONE LOOK

COLORBODY™ PORCELAIN FLOOR TILE WITH STEPWISE™ TECHNOLOGY



TRADITION HS10



NATIVE HS11



LINEAGE HS12



LEGACY HS13

COLORBODY™ PORCELAIN LANDMARK 12 x 10 HEXAGON MOSAIC TILE



TRADITION BLEND HS14



NATIVE BLEND HS15



LINEAGE BLEND HS16



LEGACY BLEND HS17

GLAZED PORCELAIN 2 x 8 FLOOR TILE WITH STEPWISE™ TECHNOLOGY



TRADITION HS10



NATIVE HS11



LINEAGE HS12



LEGACY HS13

GLAZED CERAMIC 2 x 2 MOSAIC TILE WITH STEPWISE™ TECHNOLOGY



TRADITION HS10



NATIVE HS11



LINEAGE HS12



LEGACY HS13



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT
*Not Applicable to Mesh-Mounted Mosaics



INDOOR/OUTDOOR



SIMPLICLEAN™

VISIT [AMERICANOLEAN.COM/WHYTILE](https://www.americanolean.com/whytile) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

HISTORIC LIMESTONE™

COLORBODY™ & GLAZED PORCELAIN AND GLAZED CERAMIC

AMERICAN OLEAN®

FINISHES: MATTE

USAGE

FLOOR

WALL

COUNTERTOP

SHOWER FLOOR

EXTERIOR FLOOR

MATERIAL

PC

CG

PG

PRICING

LOW

HIGH

SPECIAL FEATURES

STEPWISE™

TRUEEDGE™

REVEAL SYNC3D™

MADE IN THE U.S.A.

LARGE FORMAT

MOSAIC/DECO

ENCAUSTIC

TERRAZZO

PAVER

CUSTOMIZE

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES

			THICKNESS	FINISH	MADE IN U.S.A.
	24 x 48 Floor Tile*	23-3/8" x 46-15/16" (59.44 cm x 119.20 cm)	5/16"	M	
	24 x 24 Floor Tile*	23-3/8" x 23-3/8" (59.44 cm x 59.44 cm)	5/16"	M	
	12 x 24 Floor Tile*	11-5/8" x 23-3/8" (29.56 cm x 59.44 cm)	5/16"	M	
	6 x 24 Floor Tile♦*	5-3/4" x 23-3/8" (14.60 cm x 59.44 cm)	5/16"	M	
	2 x 8 Floor Tile*	2-1/4" x 7-15/16" (5.65 cm x 20.26 cm)	3/8"	M	
	12 x 10 Landmark Hex Tile (Mesh-mounted)	12-1/2" x 10-1/2" Sheet (30.48 cm x 33.02 cm Sheet)	5/16"	M	
	2 x 2 Mosaic Tile* (Dot-mounted)	12" x 24" Sheet (30.48 cm x 60.96 cm Sheet)	1/4"	M	

M Matte Finish ♦ StepWise™ Technology available in floor and 2 x 2 mosaic tile only.
♦ 6 x 24 and other custom sizes available through Linear Express.

INSTALLATION & PRICING

Grout Joint Recommendation	Shade Variation
Floor Tile: 1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.) 2 x 8 Floor: 3/16" Mosaic Tile: 1/8"	HIGH (V3) RANDOM (V4) (Mosaic tile only.)

PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR/LANDMARK HEX RESULT	2x2 MOSAIC RESULT
Water Absorption	C373	< 0.5%	< 3.0%
Breaking Strength	C648	> 275 lbf	> 250 lbf
Scratch Hardness	C1895	8.0	8.0
Chemical Resistance	C650	Resistant	Resistant

For additional information on test results, visit us at: americanolean.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance		
1	Residential Bathrooms	3 All Residential / Light Commercial
2	All Residential Areas	4 All Residential / Commercial

FEATURES

PRE-CONSUMER RECYCLED MATERIALS

POST-CONSUMER RECYCLED MATERIALS

REVEAL IMAGING®

CERTIFIED PORCELAIN TILE
0.05% or less water absorption

GREEN BUILDING COUNCIL MEMBER

ZEROTOX

All or select items within this series meet the requirements for these qualifications.
For more information visit americanolean.com.

TRIM

		NUMBER	FINISH
	Floor Bullnose	3 x 24	P43F9 M

M Matte Finish

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●
Wet & Level – Interior Floor	≥ 0.42	●
Shower Floors - Standard Center Drain	≥ 0.42	●*
Shower Floors - Linear Drain	≥ 0.60	●♦
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	●♦
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●
Pool Linings	N/A	●**

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Floor tile and Landmark Hex suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed. 2 x 2 mosaic suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

- * 2x2 Mosaic tile only.
- ** 2 x 8 Floor and 2 x 2 mosaic tile only.
- ♦ 12 x 24, 6 x 24, 2 x 8 floor tile and 2 x 2 mosaic tile only.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to “Factors to Consider” at: americanolean.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

888.AOT.TILE

AMERICAN OLEAN®
PROVEN IN TILE™

AMERICANOLEAN.COM

©2025 AMERICAN OLEAN (8/25)