

CONCRETE LOOK



NEOCONCRETE™

This concrete-look tile is one you can count on to deliver both style and safety in spaces that demand more. Beautiful classic coloring comes in two large sizes, designed to coordinate with one of our favorite collections—Neospeck™. Neoconcrete™ completes the offering with a rectified Colorbody™ porcelain tile available with Stepwise™ technology.



Cover photo features Neoconcrete™ Medium Gray, 12 x 24 on the floor and Ascend Stone™ Candid Heather, 4 x 4 Hexagon on the wall.
Above photo features Neoconcrete™ White 12 x 24 on the walls.

NEOCONCRETE™

COLORBODY™ PORCELAIN FLOOR WITH STEPWISE™ TECHNOLOGY

AMERICAN OLEAN®

FINISHES: MATTE | LIGHT POLISHED

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR




EXTERIOR FLOOR

MATERIAL



PC
COLORBODY PORCELAIN

PRICING



LOW HIGH

SPECIAL FEATURES



STEPWISE™



TRUEEDGE™



REVEAL SYNC3D™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

CONCRETE LOOK

COLORBODY™ PORCELAIN FLOOR TILE



WHITE NE10



BEIGE NE11



LIGHT GRAY NE12



MEDIUM GRAY NE13



50% MORE
SLIP RESISTANT
THAN ORDINARY TILE*



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT™
*Applies to products with Matte and Natural Finishes



FIRE-RESISTANT



INDOOR/OUTDOOR



SIMPLICLEAN™

VISIT [AMERICANOLEAN.COM/WHYTILE](https://www.americanolean.com/whytile) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

NEOCONCRETE™

COLORBODY™ PORCELAIN FLOOR WITH STEPWISE™ TECHNOLOGY

AMERICAN OLEAN®

FINISHES: MATTE | LIGHT POLISHED


USAGE




MATERIAL



PRICING



SPECIAL FEATURES



NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES

			THICKNESS	FINISH	MADE IN U.S.A.
	24 x 24 Floor Tile	23-3/8" x 23-3/8" (59.44 cm x 59.44 cm)	5/16"	M LP	
	12 x 24 Floor Tile	11-5/8" x 23-3/8" (29.56 cm x 59.44 cm)	5/16"	M LP	

Made in the U.S.A. designation is subject to change. Please visit americanolean.com for the most current manufacturing information.

M Matte Finish **LP** Light Polished Finish

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●
Wet & Level – Interior Floor	≥ 0.42	●*
Shower Floors - Standard Center Drain	≥ 0.42	
Shower Floors - Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	●**
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	●*
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Floor tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

* Matte floor only.

** 12 x 24 floor tile in matte finish only.

FEATURES



REVEAL IMAGING®



ZEROTOX

All or select items within this series meet the requirements for these qualifications. For more information visit americanolean.com.

CONCRETE LOOK

TRIM

			NUMBER	FINISH
	Floor Bullnose	3 x 24	P43F9	M
	Cove Base	6 x 12	P36C9TB	M
	Cove Base Outcorner	1 x 6	PC36C9TB	M

M Matte Finish

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15' or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)	 MEDIUM (V2)

PERFORMANCE CHARACTERISTICS

	ASTM#	RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbf
Scratch Hardness	C1895	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: americanolean.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit americanolean.com.

888.AOT.TILE



AMERICAN OLEAN®

AMERICANOLEAN.COM

©2026 AMERICAN OLEAN (1/26)