

# ROCHESTER™

GLAZED PORCELAIN FLOOR AND GLAZED CERAMIC MOSAIC

AMERICAN OLEAN®

STONE LOOK



AMERICAN OLEAN®  
PROVEN IN TILE™

# ROCHESTER™

Rochester is a blend of two popular natural stones, limestone and pulpis marble. The limestone provides the back drop with its soft sand-like movement and the pulpis marble provides beautiful, fine veining. The beauty of this natural stone inspired collection is enhanced by chiseled edges, creating an even more authentic look.



Cover and above photo features Beige 12 x 24 tile and 1-1/2 x 1-1/2 Hexagon Mosaic on the floor.

FINISHES: MATTE

USAGE




MATERIAL



PRICING



SPECIAL FEATURES



NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

STONE LOOK

GLAZED PORCELAIN FLOOR TILE



WHITE RC01



GRAY RC02



BEIGE RC03


HEXAGON MOSAIC TILE



WHITE RC01



GRAY RC02



BEIGE RC03



VISIT [AMERICANOLEAN.COM/WHYTILE](https://www.americanolean.com/whytile) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: MATTE

USAGE




MATERIAL



PRICING



SPECIAL FEATURES



NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

STONE LOOK

SIZES

|  |                                                 |                                                     | THICKNESS | FINISH | MADE IN U.S.A |
|--|-------------------------------------------------|-----------------------------------------------------|-----------|--------|---------------|
|  | 12 x 24 Floor Tile                              | 11-13/16" x 23-13/16" (30.00 cm x 60.48 cm)         | 5/16"     | M      |               |
|  | 1 1/2 x 1 1/2 Hexagon Mosaic Tile (Dot-mounted) | 11-3/8" x 10-1/4" Sheet (28.89 cm x 26.04 cm Sheet) | 1/4"      | M      |               |

M Matte Finish

APPLICATIONS

|                                                                                                      | TARGET DCOF WET                   | SUITABLE |
|------------------------------------------------------------------------------------------------------|-----------------------------------|----------|
| Dry & Level – Interior Floor                                                                         | N/A                               | ●        |
| Wet & Level – Interior Floor                                                                         | ≥ 0.42                            | ●        |
| Shower Floors - Standard Center Drain                                                                | ≥ 0.42                            | ●*       |
| Shower Floors - Linear Drain                                                                         | ≥ 0.42 (Mosaic)<br>≥ 0.60 (Floor) | ●*       |
| Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear) | ≥ 0.60                            |          |
| Ramps & Inclines                                                                                     | ≥ 0.65                            |          |
| Walls/Backsplashes                                                                                   | N/A                               | ●        |
| Countertops                                                                                          | N/A                               | ●        |
| Pool Linings                                                                                         | N/A                               | ●*       |

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [americanolean.com/DCOF](http://americanolean.com/DCOF).

APPLICATION NOTES:

Floor tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.  
Mosaic tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.  
\* Mosaic tile only

FEATURES



All or select items within this series meet the requirements for these qualifications. For more information visit [marazzitile.com](http://marazzitile.com).

TRIM

|  |                | NUMBER       | FINISH |
|--|----------------|--------------|--------|
|  | Floor Bullnose | 3 x 12 P43C9 | M      |

M Matte Finish

INSTALLATION & PRICING

| Grout Joint Recommendation                                                                                                                                                            | Shade Variation    |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| <p><b>Floor Tile:</b> 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)</p> <p><b>Mosaic Tile:</b> 1/8"</p> | <p>MEDIUM (V2)</p> |

PERFORMANCE CHARACTERISTICS

|                     | ASTM# | FLOOR RESULT | MOSAIC RESULT |
|---------------------|-------|--------------|---------------|
| Water Absorption    | C373  | < 0.5%       | <3.0%         |
| Breaking Strength   | C648  | > 250 lbf.   | >250 lbf.     |
| Scratch Hardness    | C1895 | 8.0          | 8.0           |
| Chemical Resistance | C650  | Resistant    | Resistant     |

For additional information on test results, visit us at: [americanolean.com/information/TestResults](http://americanolean.com/information/TestResults).

DURABILITY

| Floor Surface Wear Resistance |                       |   |                                    |
|-------------------------------|-----------------------|---|------------------------------------|
| 1                             | Residential Bathrooms | 3 | All Residential / Light Commercial |
| 2                             | All Residential Areas | 4 | All Residential / Commercial       |

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [americanolean.com/Factors](http://americanolean.com/Factors).

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [americanolean.com/LargeTiles](http://americanolean.com/LargeTiles) for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit [americanolean.com](http://americanolean.com).