

STONE THEORY™

GLAZED PORCELAIN FLOOR, GLAZED CERAMIC MOSAIC,
AND ANTIQUED MIRROR & GLASS MOSAICS

AMERICAN OLEAN®

STONE LOOK



AMERICAN OLEAN®

STONE THEORY™

Stone Theory™ blends nature with a contemporary flair. Inspired by the fusion of marble and art, the three neutral palettes are offered for both floor and wall. The stunning Gem Chevron glass and antiqued mirror mosaic, inspired by Art Deco, accentuates its intriguing chevron pattern and striking veining, creating a striking yet calming atmosphere. With Stone Theory™, you can create a bathroom that is both modern and timeless.



Cover photo features Stone Theory™ Gem Chevron Glass & Antiqued Mirror Mosaic on the wall and Mythique Marble™ Majestic, 12 x 24 on the floor. Above photo features Stone Theory™ Notion, 12 x 24 on the floor, and Color Story™ Wall Restore, 4 x 12 on the wall.

STONE THEORY™

GLAZED PORCELAIN FLOOR, GLAZED CERAMIC MOSAIC,
AND ANTIQUED MIRROR & GLASS MOSAICS

AMERICAN OLEAN®

FINISHES: MATTE | GLOSSY

USAGE	MATERIAL	PRICING	SPECIAL FEATURES
 FLOOR  WALL  COUNTERTOP  SHOWER FLOOR  EXTERIOR FLOOR	 PG  CG  MX	 LOW HIGH	 STEPWISE™  TRUEDGE™  REVEAL SYNC3D™  MADE IN THE U.S.A.  LARGE FORMAT  MOSAIC/DECO  ENCAUSTIC  TERRAZZO  PAVER  CUSTOMIZE

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

STONE LOOK

GLAZED PORCELAIN FLOOR TILE



NOTION ST86



METAMORPHIC ST87



FORMATION ST88

GLAZED CERAMIC 2 x 2 MOSAIC



NOTION ST86



METAMORPHIC ST87



FORMATION ST88

STACK GLASS & ANTIQUED MIRROR MOSAIC



GEO STACK MOSAIC ST89



GEM STACK MOSAICS ST96

ARROW GLASS & ANTIQUED MIRROR MOSAIC



GEO ARROW MOSAIC ST89



GEM ARROW MOSAIC ST96

CHEVRON GLASS & ANTIQUED MIRROR MOSAIC



GEO CHEVRON MOSAIC ST89



GEMCHEVRON MOSAIC ST96



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT

Applicable to products with Matte and Textured finishes



FIRE-RESISTANT

Not Applicable to Mesh-Mounted Mosaic



CLIMATEPRO™



SIMPLICLEAN™

VISIT [AMERICANOLEAN.COM/WHYTILE](https://www.americanolean.com/whytile) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

STONE THEORY™

GLAZED PORCELAIN FLOOR, GLAZED CERAMIC MOSAIC,
AND ANTIQUED MIRROR & GLASS MOSAICS

AMERICAN OLEAN®

FINISHES: MATTE | GLOSSY

USAGE

 FLOOR

 WALL

 COUNTERTOP

 SHOWER FLOOR

 EXTERIOR FLOOR

MATERIAL

 PG GLAZED PORCELAIN

 CG GLAZED CERAMIC

 MX MIXED MATERIALS

PRICING

 LOW HIGH

SPECIAL FEATURES

 STEPWISE*

 TRUEEDGE*

 REVEAL SYNC3D*

 MADE IN THE U.S.A.

 LARGE FORMAT

 MOSAIC/DECO

 ENCAUSTIC

 TERRAZZO

 PAVER

 CUSTOMIZE

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

STONE LOOK

SIZES

			THICKNESS	FINISH	MADE IN U.S.A.
	12 x 24 Floor Tile	11-7/8" x 23-5/8" (30.23 cm x 60.12 cm)	5/16"	M	
	2 x 2 Mosaic (Dot-mounted)	12" x 24" Sheet (30.48 cm x 60.96 cm Sheet)	1/4"	M	
	Arrow Glass & Antiqued Mirror Mosaic (Mesh-mounted)	13-15/16" x 11-1/2" Sheet (35.51 cm x 29.31 cm Sheet)	3/16"	G	
	Chevron Glass & Antiqued Mirror Mosaic (Mesh-mounted)	14-1/16" x 12" Sheet (35.71 cm x 30.48 cm Sheet)	3/16"	G	
	Stack Glass & Antiqued Mirror Mosaic (Mesh-mounted)	13-15/16" x 12-1/4" Sheet (35.51 cm x 31.00 cm Sheet)	3/16"	G	

Made in the U.S.A. designation is subject to change. Please visit americanolean.com for the most current manufacturing information.

M Matte Finish G Glossy Finish

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	*
Wet & Level – Interior Floor	≥ 0.42	*
Shower Floors – Standard Center Drain	≥ 0.42	**
Shower Floors - Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	**
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●*
Pool Linings	N/A	●**

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Floor tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Mosaic tiles suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

* Floor and 2 x 2 mosaic tile only.

** 2 x 2 mosaic tile only.

TRIM

		NUMBER	FINISH
	Floor Bullnose	3 x 12	P43C9 M

M Matte Finish

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor Tile: 3/16" (Overlap should not exceed 33% when installing tile with length 15" or greater in a staggered brick-joint pattern.) Mosaic Tile: 1/8"	 MEDIUM (V2)

PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT	2 x 2 MOSAIC RESULT	GLASS AND ANTIQUED MIRROR MOSAIC RESULT
Water Absorption	C373	< 0.5%	< 3.0%	< 0.5%
Breaking Strength	C648	> 275 lbf	> 250 lbf	> 100 lbf
Scratch Hardness	C1895	8.0	8.0	4.0
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: americanolean.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit americanolean.com.

FEATURES

 PRE-CONSUMER RECYCLED MATERIALS

 POST-CONSUMER RECYCLED MATERIALS

 REVEAL IMAGING®



ZEROTOX

All or select items within this series meet the requirements for these qualifications.
For more information visit americanolean.com.

888.AOT.TILE



AMERICAN OLEAN®

AMERICANOLEAN.COM

©2026 AMERICAN OLEAN (01/26)