

VERO™
COLORBODY™ PORCELAIN

MARAZZI®
DARE TO BE BOLD™

WOOD LOOK



VERO™

Vero™ effortlessly celebrates the origins of natural style. This oak-inspired collection satisfies the senses of sight and touch thanks to its authentic likeness to natural wood. Vero introduces an extra-long 9x71 plank size and includes a 4x21 chevron plank tile, showing off wood visuals in an exceptional size package. Capture the understated elegance of wood with a gentle time-worn look.



COVER PHOTO: ROVERE
ABOVE PHOTO: CASTAGNO

WOOD LOOK

FINISHES: MATTE

USAGE



MATERIAL



PRICING



SPECIAL FEATURES



STEPWISE TRUEDGE™ MADE IN THE U.S.A. MOSAIC/DECO ENCAUSTIC ENCAUSTIC PAVER CUSTOMIZE

WOOD LOOK

SEE CHARTS FOR FULL PRODUCT DETAILS.

9 x 71 FLOOR TILE



VR20 Natural



VR21 Rovere



VR22 Castagno



VR23 Quercia

4 x 21 FLOOR TILE



VR20 Natural



VR21 Rovere



VR22 Castagno



VR23 Quercia



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



CLIMATEPRO™



SIMPLICLEAN™

VISIT [MARAZZITILE.COM/WHYTILE](https://marazzitile.com/whytile) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.



LEARN MORE

FINISHES: MATTE

USAGE



MATERIAL



PRICING



SPECIAL FEATURES



STEPWISE

TRUEEDGE™

MADE IN THE U.S.A.



LARGE FORMAT

MOSAIC/DECO

ENCAUSTIC

ENCAUSTIC

PAVER

CUSTOMIZE

WOOD LOOK

SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
 9 x 71 Floor Tile	8-3/4" x 70-3/4" (22.30 cm x 179.80 cm)	3/8"	17.27	4
 4 x 21 Floor Tile	4-5/16" x 21-1/4" (11.00 cm x 54.00 cm)	3/8"	10.12	18

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	■
Wet & Level – Interior Floor	≥ 0.42	■
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit marazzitile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor Tile: 9" x 71": 1/8" (3/16" when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.) 4" x 21": 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)	V2 Medium Variation

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: marazzitile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	③	All Residential /Light Commercial*
2	Residential Areas	④	All Residential / Commercial**

* 4 x 21 floor tile only.

** 9 x 71 floor tile only.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazzitile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to marazzitile.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

FEATURES



PRE-CONSUMER
RECYCLED MATERIALS



REVEAL IMAGING®



CERTIFIED
PORCELAIN
60% or more content is TILE

ZEROTOX
Healthy Homes | Healthy Planet

All or select items within this series meet the requirements for these qualifications. For more information visit marazzitile.com.